

SERIES: PDRA-240 | **DESCRIPTION:** AC-DC POWER SUPPLY


FEATURES

- up to 240 W continuous power
- universal input voltage range
- over current, over voltage, input under voltage, short circuit, and over temperature protections
- active power factor correction
- remote on/off control
- output trim
- low ripple and noise
- -25 to +70°C temperature range
- UL/cUL 60950-1 safety approval
- efficiency up to 93%



| MODEL | output voltage | output current | output power | ripple and noise ¹ | efficiency ² |
|-------------|----------------|----------------|--------------|-------------------------------|-------------------------|
| | (Vdc) | max (A) | max (W) | max (mVp-p) | typ (%) |
| PDRA-240-24 | 24 | 10 | 240 | 100 | 92 |
| PDRA-240-48 | 48 | 5 | 240 | 150 | 93 |

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with a 1 μ F ceramic and 10 μ F electrolytic capacitor on the output.
 2. At 230 Vac input.
 3. All specifications are measured at Ta=25°C, humidity <75%, nominal input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY


INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|-------------------------------|-----|------|-----|-------|
| voltage | | 85 | | 264 | Vac |
| | | 120 | | 370 | Vdc |
| frequency | | 47 | | 63 | Hz |
| under voltage protection | start-up voltage at full load | 75 | | 83 | Vac |
| | shutdown voltage at full load | 67 | | 74 | Vac |
| current | at 115 Vac | | | 3.0 | A |
| | at 230 Vac | | | 1.5 | A |
| inrush current | at 115 Vac | | 30 | | A |
| | at 230 Vac | | 60 | | A |
| power factor correction | at 115 Vac | | 0.98 | | |
| | at 230 Vac | | 0.96 | | |
| no load power consumption | | | 1.0 | | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|------------------------|-----|-------|-------|-------|
| capacitive load | 24 Vdc output model | | | 4,700 | µF |
| | 48 Vdc output model | | | 2,700 | µF |
| initial set point accuracy | | | | ±1 | % |
| line regulation | at full load | | | ±0.5 | % |
| load regulation | from 5~100% load | | | ±1 | % |
| adjustability ¹ | via built in trim pot | | | | |
| | 24 Vdc output model | 24 | | 28 | Vdc |
| | 48 Vdc output model | 48 | | 52.8 | Vdc |
| start-up time | | | | 1.5 | s |
| hold-up time | at 115/230 Vac | | 22 | | ms |
| switching frequency | | | 100 | | kHz |
| temperature coefficient | | | ±0.03 | | %/°C |

Notes: 1. Max output power of 240 W.

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|-----------------------------|--------------------------------|-----|-----|-----|-------|
| over voltage protection | continuous, auto recovery | | | | |
| over current protection | auto recovery | 110 | | 150 | % |
| short circuit protection | continuous, auto recovery | | | | |
| over temperature protection | output shutdown, auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---------------------|--|-------|-----|-----|-------|
| isolation voltage | input to output for 1 minute | 3,000 | | | Vac |
| | input to ground for 1 minute | 1,500 | | | Vac |
| | output to ground for 1 minute | 500 | | | Vac |
| safety approvals | UL 60950-1, EN 60950-1 | | | | |
| safety class | class I | | | | |
| EMI/EMC | EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3 | | | | |
| conducted emissions | CISPR22/EN55022, Class B | | | | |
| radiated emissions | CISPR22/EN55022, Class B | | | | |
| ESD | IEC/EN61000-4-2, contact ±6 kV/ air ±8 kV, Class B | | | | |
| radiated immunity | IEC/EN61000-4-3, 10 V/m, Class A | | | | |
| EFT/burst | IEC/EN61000-4-4, ±4 kV, Class B | | | | |

Notes: 2. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

SAFETY & COMPLIANCE (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|---------|-----|-----|-------|
| surge | IEC/EN61000-4-5, line to line ± 2 kV/ line to ground ± 4 kV, Class B | | | | |
| conducted immunity | IEC/EN61000-4-6, 10 Vr.m.s, Class A | | | | |
| PFM | IEC/EN61000-4-8, 10 A/m, Class A | | | | |
| voltage dips & interruptions | IEC/EN61000-4-11, 0%-70%, Class B | | | | |
| MTBF | as per MIL-HDBK-217F at 25 °C | 300,000 | | | hours |
| RoHS | 2011/65/EU | | | | |

Notes: 1. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curves | -25 | | 70 | °C |
| storage temperature | | -25 | | 85 | °C |
| storage humidity | non-condensing | | | 95 | % |


MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|---|-----|-----|-----|-------|
| dimensions | 60.00 x 125.00 x 120.00 (2.36 x 4.92 x 4.72 inches) | | | | mm |
| material | heat resistant plastic (UL94V-0) and metal | | | | |
| weight | | | 820 | | g |


MECHANICAL DRAWING

units: mm [inch]
tolerance: $\pm 1.00[\pm 0.040]$

wire range: 26~10 AWG
strip length: 8.0 mm
mounts to DIN RAIL TS35
tightening torque: max 0.4 N*m

| TERMINAL CONNECTIONS | |
|----------------------|---|
| TERMINAL | Function |
| 1 | +Vout |
| 2 | +Vout |
| 3 | -Vout |
| 4 | -Vout |
| 5 | AC(N) |
| 6 | AC(L) |
| 7 |  |


| CONTROL TERMINAL | |
|------------------|----------|
| TERMINAL | Function |
| 1 | +CTRL |
| 2 | -CTRL |




Note: 2. Rail needs to connect to safety ground.

DERATING CURVES

load vs. ambient temperature
(at 85~264 Vac / 120~370 Vdc input voltage)




load vs. input voltage
(at 25°C)




EFFICIENCY CURVES


PDRA-240-24 Efficiency Curve
(Efficiency vs. Input Voltage)




PDRA-240-24 Efficiency Curve
(Efficiency vs. Load Current)



PDRA-240-48 Efficiency Curve
(Efficiency vs. Input Voltage)



PDRA-240-48 Efficiency Curve
(Efficiency vs. Load Current)



APPLICATION CIRCUIT

Figure 1 Typical Application Circuit





Figure 2 Remote Control Applications Circuit



The power supply can be turned on/off by using the "CTRL" terminals.
 Enable output: open
 Disable output: 4.5~12.5 Vdc

REVISION HISTORY

| rev. | description | date |
|------|---------------------------|------------|
| 1.0 | initial release | 10/17/2016 |
| 1.01 | added 48 Vdc output model | 02/01/2018 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.